



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE **TMP5705**

2. DESCRIPTION 5 Core 7/.5 (1.5sqmm) .P.C.W. UV stabilised polypropylene insulated.
Score and snap UV stabilised TYFLO MP. sheathed irrigation cable.
Extra Low Voltage . Not for Mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 7 strands of 0.5mm Annealed Copper to
AS1125 drawn from Class 102 copper to AS1574.
Max. D.C. resistance at 20C : 13.6 ohms / km

3.2 INSULATION : Coloured UV stabilised polypropylene
Nominal Diameter : 2.35 mm
Nom. Wall Thickness: 0.4 mm

3.3 LAY UP 5 Cores twisted .
1. Black 2 Red 3. White 4. Blue 5. Green

3.4 SHEATH Score and snap UV stabilised TYFLO MP.
Nominal Diameter : 7.7 mm
Nom. Wall Thickness : 0.6 mm