

# Twin Trurip Speaker Cable (LFC, LFX)

V75 PVC insulated

## Applications

Theatre Systems (Residential and Commercial)

## Product Specifications

### Construction:

**Conductor:** Plain Annealed Copper to AS/NZS1125

Drawn from Class 102 Oxygen Free copper to AS/NZS1574

**Insulation:** Coloured/Clear V75 PVC to AS/NZS 3808

**Sheath:** N/A

**Relevant Standard:** AS/NZS1125, AS/NZS1574, AS/NZS3808



Code	No. of Cores	Nominal Area (mm <sup>2</sup> )	Strand No. / Size	Electrical Resistance @ 20°C (Ω/KM)	Nominal OD
LFC2702	2	0.22	7/0.2	89	1.4 x 3.0
LFC21402	2	0.44	14/0.2	44.8	1.75 x 3.8
LFC22402	2	0.75	24/0.2	26.5	2.4 x 5.2
LFC26502	2	2	64/0.2	9.1	3.35 x 7.2
LFC28402	2	2.64	84/0.2	7.1	4.25 x 9.0
<b>Clear Super Speaker</b>					
LFX22402	2	0.75	24/0.2	26.5	2.3 x 5.0
LFX24802	2	1.5	48/0.2	13.3	3.1 x 6.5
LFX26502	2	2	65/0.2	9.1	3.35 x 7.2
LFX28402	2	2.64	84/0.2	7.1	4.2 x 9.0
LFX210502	2	3.3	105/0.2	7.1	4.2 x 8.7
LFX219202	2	6	192/0.2	5.6	5.5 x 11.5