

Tysonic 100v Line Speaker Flex (LMC)

V75 PVC insulated

Applications

100v Line PA & Theatre Systems (Residential and Commercial)

Product Specifications

Construction:

Conductor: Plain Annealed Copper to AS/NZS1125

Drawn from Class 102 Oxygen Free copper to AS/NZS1574

Insulation: Coloured V75 PVC to AS/NZS 3808

Sheath: Coloured Flame Retardant, UV – Resistant, Low Smoke and Low Halogen PVC.

Relevant Standard: AS/NZS1125, AS/NZS1574, AS/NZS3808

Core Configuration:

2 Core: 1. Red, 2. Black

4 Core: 1. Red, 2. Black, 3. White, 4. Green



Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Electrical Resistance @ 20°C (Ω/KM)	Nominal OD
LMC02/1.3	2	1.3	65/0.16	13.7	6.3
LMC04/1.3	4	1.3	65/0.16	13.7	7.1
LMC02/1.5	2	1.5	30/.25	13.3	7.1
LMC04/1.5	4	1.5	30/.25	13.3	8.1
LMC02/2.1	2	2.1	105/0.16	8.6	7.3
LMC04/2.1	4	2.1	105/0.16	8.6	8.5
LMC02/3.3	2	3.3	67/0.25	5.6	8.4
LMC04/3.3	4	3.3	67/0.25	5.6	9.2
Screened Cable					
LMS2/0.37	2	0.37	21/0.15	50	3.95