



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE WMW137043

2. DESCRIPTION 13 Core 7/.43 (1.0sqmm) .P.C.W. UV stabilised polypropylene insulated.
4V75 P.V.C. sheathed . TYFLO irrigation cable.
Extra Low Voltage . Not for Mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 7 strands of 0.43mm Annealed Copper to
AS1125 drawn from Class 102 copper to
AS1574. Max. D.C. resistance at 20C : 21.2 ohms / km

3.2 INSULATION : Coloured UV stabilised polypropylene
Nominal Diameter : 2.15 mm
Nom. Wall Thickness: 0.4 mm

3.3 LAY UP 13 Cores twisted .
1. Black 2 Red 3. White 4. Blue 5. Green
6. Brown 7. Yellow 8. Pink 9. Grey 10. Violet
11. Beige 12. Light Green 13. Orange

3.4 SHEATH Coloured P.V.C. type 4V75 to AS3808.
Nominal Diameter : 10.7 mm
Nom. Wall Thickness : 0.7 mm