



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1.PRODUCT CODE** **WMW27085**
- 2. DESCRIPTION** 2 Core 7/.85 (4 sqmm) .P.C.W. UV stabilised polypropylene insulated.
4V75 P.V.C. sheathed . TYFLO irrigation cable.
Extra Low Voltage . Not for Mains connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR :** 7 strands of 0.67mm Annealed Copper to
AS1125 drawn from Class 102 copper to
AS1574. Max. D.C. resistance at 20C : 4.6 ohms / km
- 3.2 INSULATION :** Coloured UV stabilised polypropylene
Nominal Diameter : 3.8 mm
Nom. Wall Thickness: 0.6 mm
- 3.3 LAY UP** 2 Cores twisted .
1. Black 2 Red
- 3.4 SHEATH** Coloured P.V.C. type 4V75 to AS3808.
Nominal Diameter : 9.2 mm
Nom. Wall Thickness : 0.7 mm