



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE WMW3703

2. DESCRIPTION 3 Core 7/3 (0.5sqmm) .P.C.W. UV stabilised polypropylene insulated.
4V75 P.V.C. sheathed . TYFLO irrigation cable.
Extra Low Voltage . Not for Mains connection.

3. CONSTRUCTION

3.1 CONDUCTOR : 7 strands of 0.3mm Annealed Copper to
AS1125 drawn from Class 102 copper to
AS1574. Max. D.C. resistance at 20C : 37.0 ohms / km

3.2 INSULATION : Coloured UV stabilised polypropylene
Nominal Diameter : 1.6 mm
Nom. Wall Thickness: 0.3 mm

3.3 LAY UP 3 Cores twisted .
1. Black 2 Red 3. White

3.4 SHEATH Coloured P.V.C. type 4V75 to AS3808.
Nominal Diameter : 4.6 mm
Nom. Wall Thickness : 0.6 mm