



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



- 1. PRODUCT CODE** **ZDU151102**
- 2. DESCRIPTION** **16.0 mmsq Plain Copper Nitrile modified V90HT PVC Insulated and Sheathed single core 0.6/1KV to AS/NZS 5000 For fixed application with FLEXIBLE conductor. RoHS compliant. Oxygen Free Copper.**
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 0.2 mm nom Plain Annealed Copper to AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.
Max. D.C. resistance at 20C: 1.21 ohms / km
- 3.2 INSULATION:** Coloured Nitrile modified P.V.C. type V90HT to AS/NZS 3808
Nominal Diameter: 7.25 mm
Nominal Wall Thickness: 1.0 mm
- 3.3 SHEATH:** Coloured Nitrile modified P.V.C. type V90HT to AS/NZS 3808
Nominal Diameter: 10.1 mm
Nominal Wall Thickness: 1.4 mm
- 3.4 IDENTIFICATION:** Embossed at intervals not exceeding 200mm
"TYCAB 16 mmsq 2009 V90HT ELECTRIC CABLE 0.6/1KV"
- 4. REFERENCE STANDARDS**
- 4.1 AS/NZS 1125** Max. conductor Resistance
- 4.2 AS/NZS 3808** **PVC** compound type.
- 4.3 AS/NZS 5000** Construction to 0.6/1KV SHEATHED SINGLE CORE
- 4.4 AS/NZS 3008** Power Amp Ratings
Voltage Drop
Derating Factors

AUSTRALIAN MADE CABLES LEADING THE WAY