




## TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833  
A.C.N. 100 305 833  
269 FRANKSTON-DANDENONG ROAD  
(LOCKED BAG 1413)  
DANDENONG STH VICTORIA 3164  
TELEPHONE 03 (Int. 613) 8791 0300  
FAX - ADMIN 03 (Int. 613) 9794 0031  
CUSTOMER SERVICE  
PHONE 03 (Int. 613) 8791 0333  
FAX 03 (Int. 613) 9791 8732  
[www.tycab.com.au](http://www.tycab.com.au)

### PRODUCT SPECIFICATION



**1. PRODUCT CODE**      **ABC1612032**

**2. DESCRIPTION**      **0 B&S BATTERY CABLE**  
**Plain Copper 60Volt V90 PVC. Not for Mains Connection.**  
**Oxygen Free Copper. RoHS compliant PVC.**

#### 3. CONSTRUCTION

**3.1 CONDUCTOR:**      **608** strands of 0.32mm Plain Annealed Copper to AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.  
Max. D.C. resistance at 20C:      0.4 ohms / km  
TYPICAL conductor diameter:      9.3 mm

**3.2 INSULATION:**      Coloured P.V.C. type V90 to AS/NZS 3808  
Nominal Diameter:      12.7 mm  
Nominal Wall Thickness:      1.7 mm

#### 4. REFERENCE STANDARDS

**4.1 AS/NZS3808**      **PVC** compound type.

**4.2 AS/NZS1125**      Conductor Tolerances

**4.3 AS/NZS1574**      Copper Type

**4.4 SAE J1127**      Minimum cross-section conductor area and Minimum Wall Thickness

**AUSTRALIAN MADE CABLES LEADING THE WAY**