



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** ATH765032
- 2. DESCRIPTION** 7 Core 65/.32 (5.2mmsq). P.C.W. V90 PVC insulated,
V90 PVC sheathed Trailer cable.
NOT FOR MAINS CONNECTION.

3. CONSTRUCTION

3.1 CONDUCTOR: 65 strands of 0.32mm Plain Annealed Copper to AS/NZS1125
drawn from Class 110A copper to AS/NZS1574

Max. D.C. Resistance at 20C: 3.5 ohms per km

3.2 INSULATION: Coloured V90 PVC to AS/NZS3808.
Nominal Diameter: 4.35mm
Nominal Wall Thickness: 0.6mm

3.3 LAY UP: 7X65/.32 Cores
1. Black
2. Yellow
3. Red
4. Green
5. Brown
6. Blue
7. White (centre core)

3.4 SHEATH: Coloured P.V.C. type V90 to AS/NZS3808.
Nominal Diameter: 16.2 mm.
Nominal Wall Thickness: 1.5 mm

FINISH TYPICALLY ROPY

AUSTRALIAN MADE CABLES LEADING THE WAY