



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION



1. PRODUCT CODE: AWC21603

2. DESCRIPTION 2 Core Flat Twin Sheathed 14/32 (1.13 mm sq). P.A.C.W.
V90 Insulated & 5V90 Sheathed Automotive.
Extra Low Voltage, Not for Mains Connection.

3. CONSTRUCTION

3.1 CONDUCTOR: 14 strands of 0.32mm Plain Annealed Copper to AS/NZS1125
drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 16.5 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS/NZS3808.

Nominal Diameter: 2.15 mm

Nominal Wall Thickness: 0.4 mm

3.3 CORE COLOURS: 1. Red
2. Black
Laid parallel

3.4 SHEATH: Coloured 5V90 to AS/NZS3808
Flat configuration

Nominal Dimensions: 3.3 x 5.5 mm

Nominal Wall Thickness: 0.6 mm

AUSTRALIAN MADE CABLES LEADING THE WAY