



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** FRL22402
- 2. DESCRIPTION** 2 Core 24/.20 (0.75 mmsq, 7.5amp). P.C.W.
V90 PVC insulated & 5V90 P.V.C. sheathed Light Duty Flexible cord.
250/250 Volt to AS/NZS3191
SEC APPROVAL V98005.
Oxygen Free Copper. RoHS Compliant PVC.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** 24 strands of 0.2 mm Annealed Copper to AS/NZS1125
drawn from Class 102 copper to AS/NZS1574.
Max. D.C. resistance at 20C: 26.0 ohms / km
- 3.2 INSULATION:** Coloured V90 PVC to AS/NZS3808.
Nominal Diameter: 2.1 mm
Nominal Wall Thickness: 0.5 mm
- 3.3 LAY UP:** 2 Cores laid up.
1. Brown
2. Blue
- 3.4 SHEATH:** Coloured P.V.C. type 5V90 to AS/NZS3808.
Nominal Diameter: 5.6 mm
Nominal Wall Thickness: 0.6 mm
- 3.5 IDENTIFICATION** Printed on sheath in contrasting colour at intervals not
exceeding 500mm.
"TYCAB V90 APP V98005 250/250V LIGHT DUTY"

AUSTRALIAN MADE CABLES LEADING THE WAY