



## **TYCAB AUSTRALIA PTY LTD**

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD  
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

[www.tycab.com.au](http://www.tycab.com.au)

## **PRODUCT SPECIFICATION**

**1. PRODUCT CODE** LFX210502

**2. DESCRIPTION** 2 Core Parallel Webbed (Figure 8) 105/.2 (3.3mmsq).  
Oxygen Free P.A.C.W. Clear P.V.C insulated Speaker cable.  
Extra Low Voltage. Not for mains connection.  
RoHS compliant PVC.

### **3. CONSTRUCTION**

**3.1 CONDUCTOR:** 105 strands of 0.2mm Plain Annealed Copper to  
AS/NZS 1125 drawn from Class 102 copper to AS/NZS 1574.

Max. D.C. resistance at 20C: 5.6 ohms / km

**3.2 INSULATION:** CLEAR P.V.C. type V90HT to AS/NZS 3808  
Parallel Webbed (Figure 8) construction

Nominal Diameter: 4.2 x 8.7 mm

Nominal Wall Thickness: 0.8 mm

**3.3 POLARITY IDENTIFICATION:** By extruded stripe on one leg.

**3.4 PRINTING:** No printing

**AUSTRALIAN MADE CABLES LEADING THE WAY**