



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833
A.C.N. 100 305 833
269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)
DANDENONG STH VICTORIA 3164
TELEPHONE 03 (Int. 613) 8791 0300
FAX - ADMIN 03 (Int. 613) 9794 0031
CUSTOMER SERVICE
PHONE 03 (Int. 613) 8791 0333
FAX 03 (Int. 613) 9791 8732
www.tycab.com.au

PRODUCT SPECIFICATION

- 1. PRODUCT CODE** LPC26/24
- 2. DESCRIPTION** 4 Core Audio cable. 2 Cores 84/0.3 (6.0mmsq) plus 2 Cores 56/0.3 (4.0mmsq).
P.A.C.W. P.V.C insulated and PVC sheathed.
Low Voltage cable. Not for mains outlet connection.
- 3. CONSTRUCTION**
- 3.1 CONDUCTOR:** **84/0.3 cores**
84/0.3 strands of 0.3mm Plain Annealed Copper to AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 3.3 ohms / km
- 56/0.3 cores**
56/0.3 strands of 0.3mm Plain Annealed Copper to AS/NZS1125 drawn from Class 110A copper to AS/NZS1574.

Max. D.C. resistance at 20C: 5.0 ohms / km
- 3.2 INSULATION:** **84/0.3 cores**
Coloured type V75 P.V.C. to AS/NZS3808.

Core 1: Red Core 2: Red/White

Nominal Diameter: 4.95 mm
Nominal Wall Thickness: 0.8 mm
- 56/0.3 cores**
Coloured type V75 P.V.C. to AS/NZS3808.

Core 3: Blue Core 4: Blue/White

Nominal Diameter: 4.35 mm
Nominal Wall Thickness: 0.8 mm
- 3.3 SHEATH:** Coloured PVC type 4V75 to AS/NZS3808

Nominal Diameter: 14.2 mm
Nominal Wall Thickness: 1.46 mm
- 3.4 IDENTIFICATION:** Printed on sheath: **TYCAB CINEMASOUND LPC26/24**

AUSTRALIAN MADE CABLES LEADING THE WAY