



## **TYCAB AUSTRALIA PTY LTD**

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

[www.tycab.com.au](http://www.tycab.com.au)

### **PRODUCT SPECIFICATION**

**1.PRODUCT CODE**     **SEC2704**

**2. DESCRIPTION**     2 Core 7/4 (.0.85 mm sq) .P.A.C.W. V75 P.V.C insulated.  
75c P.V.C. sheathed .  
Extra Low Voltage . Not for mains outlet connection.  
Oxygen Free Copper . RoHS compliant PVC.

#### **3. CONSTRUCTION**

**3.1 CONDUCTOR :**     7 strands of 0.4 mm Plain Annealed Copper to  
AS1125 drawn from Class 102 copper to  
AS1574. Max. D.C. resistance at 20C : 23.0 ohms / klm

**3.2 INSULATION :**    Coloured 75 C P.V.C.to AS3808..  
Nominal Diameter : 2.0 mm  
Nom. Wall Thickness: 0.4 mm

**3.3 LAY UP**           2 Cores Twisted .

1. Red     2. Black

**3.4 SHEATH**           Coloured P.V.C. type V75 C to AS3808  
Nominal Diameter : 5.1 mm  
Nom. Wall Thickness : 0.5 mm

TYPICAL ROPY FINISH

#### **3.5 IDENTIFICATION**

Nil

Or by request