



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1.PRODUCT CODE **WWS21178**

2. DESCRIPTION 2 Core Flat IRRIGATION control cable 1.78 (2.5 mm sq) .T.A.C.W.
75c P.V.C insulated & UV Stabilised Polypropylene Sheathed.
Extra Low Voltage Not for Mains GPO Connection.
Maxi Cable .

3. CONSTRUCTION

3.1 CONDUCTOR : 1 strands of 1.78 mm **Tinned** Annealed Copper to
AS1125 drawn from Class 110A copper to AS1574.

Max. D.C. resistance at 20C : 7.35 ohms / klm

3.2 INSULATION : Coloured V75 P.V.C. to AS3808

Nominal Diameter : 4.8mm

Nom. Wall Thickness: 1.5mm

3.3 CORE COLOURS

1. Red 2. Black

3.4 SHEATH : Coloured UV Stabilised Polypropylene .
Flat configuration

Nominal Dimensions :7.5 x 12.5 mm

Nom. Wall Thickness : 1.15 mm