



TYCAB AUSTRALIA PTY LTD

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD

(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au

PRODUCT SPECIFICATION

1. PRODUCT CODE WWS27067

2. DESCRIPTION 2 Core Flat IRRIGATION control cable 0.67 (2.5mmsq). T.A.C.W.
75C P.V.C insulated & UV Stabilised Polypropylene sheathed.
Extra Low Voltage. Not for Mains GPO Connection.
Maxi cable.

3. CONSTRUCTION

3.1 CONDUCTOR: 7 strands of 0.67mm **Tinned** Annealed Copper to
AS1125 drawn from Class 110A copper to AS1574.

Max. D.C. resistance at 20C: 7.56 ohms / km

3.2 INSULATION: Coloured V75 P.V.C to AS3808.

Nominal Diameter: 5.0 mm

Nominal Wall Thickness: 1.5 mm

3.3 CORE COLOURS: 1. Red
2. Black

3.4 SHEATH: Coloured UV Stabilised Polypropylene.
Flat Configuration

Nominal Diameter: 7.7 x 12.7 mm

Nominal Wall Thickness: 1.15 mm