



## **TYSONIC SPEAKER FLEX**

### **PRODUCT SPECIFICATION**

**1.PRODUCT CODE** LMC02/3.3

**2. DESCRIPTION** 2 Core 41/32 (3.3mm sq nom.) T.C.W. V75 P.V.C insulated.  
HBZRH-80FZW Low smoke, Low Halogen P.V.C. sheathed .  
Tysonic Speaker Flex.  
Oxygen free copper . RoHS compliant .

### **3. CONSTRUCTION**

**3.1 CONDUCTOR :** 41 strands of 0.32 mm Annealed Copper to  
AS/NZS1125 drawn from Class 102 copper to AS/NZS1574.  
Max. D.C. resistance at 20C : 5.6 ohms / km

**3.2 INSULATION :** Coloured V75 PVC to AS/NZS3808  
Nominal Diameter : 2.5 mm  
Nom. Wall Thickness: 0.60 mm

**3.3 LAY UP** 2 Cores.  
1. Red plus 2. Black

**3.4 SHEATH** Coloured P.V.C. type HBZRH-80FZW  
Nominal Diameter : 8.4 mm  
Nom. Wall Thickness : 1.0 mm

### **3.4 IDENTIFICATION**

Printed at max 1000mm spacings

Cable to be meter marked, i.e every 1 meter

TYCAB NZ Y.O.M. – 3.3mm<sup>2</sup> 12AWG 2 CORE 100V LINE SPEAKER CABLE M|M