

AUDIO CABLE

PAGE 1

TWIN TRURIP SPEAKER CABLE

PAGE 2

TYSONIC 100V LINE SPEAKER FLEX

PAGE 3

TYCAB CINEMA SOUND CABLE



Twin Trurip Speaker Cable (LFC, LFX)

V75 PVC insulated

Applications

Theatre Systems (Residential and Commercial)

Product Specifications

Construction:

Conductor: Plain Annealed Copper to AS/NZS1125

Drawn from Class 102 Oxygen Free copper to AS/NZS1574

Insulation: Coloured/Clear V75 PVC to AS/NZS 3808

Sheath: N/A

Relevant Standard: AS/NZS1125, AS/NZS1574, AS/NZS3808



Current Code	New Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Electrical Resistance @ 20°c (Ω/KM)	Nominal OD
LFC2702	SPFE-0.2	2	0.22	7/0.2	89	1.4 x 3.0
LFC22402	SPFE-0.75	2	0.75	24/0.2	26.5	2.4 x 5.2
Clear Super Speaker						
LFX22402	SPCE-0.75	2	0.75	24/0.2	26.5	2.3 x 5.0
LFX24802	SPCE-1.5	2	1.5	48/0.2	13.3	3.1 x 6.5
LFX26502	SPCE-2	2	2	65/0.2	9.1	3.35 x 7.2

Tysonic 100v Line Speaker Flex (LMC)

V75 PVC insulated

Applications

100v Line PA & Theatre Systems (Residential and Commercial)

Product Specifications

Construction:

Conductor: Plain Annealed Copper to AS/NZS1125

Drawn from Class 102 Oxygen Free copper to AS/NZS1574

Insulation: Coloured V75 PVC to AS/NZS 3808

Sheath: Coloured Flame Retardant, UV – Resistant, Low Smoke and Low Halogen PVC.

Relevant Standard: AS/NZS1125, AS/NZS1574, AS/NZS3808

Core Configuration:

2 Core: 1. Red, 2. Black

4 Core: 1. Red, 2. Black, 3. White, 4. Green



Code	No. of Cores	Nominal Area (mm²)	Strand No. / Size	Electrical Resistance @ 20°C (Ω/KM)	Nominal OD
LMC02/1.3	2	1.3	65/0.16	13.7	6.3
LMC04/1.3	4	1.3	65/0.16	13.7	7.1
LMC02/2.1	2	2.1	105/0.16	8.6	7.3
LMC04/2.1	4	2.1	105/0.16	8.6	8.5

Tycab Cinema Sound Cable (LPC)

V75 PVC insulated

Applications

Specified Cinema Cable

Product Specifications

Construction:

Conductor: Plain Annealed Copper to AS/NZS1125

Drawn from Class 110A Oxygen Free copper to AS/NZS1574

Insulation: Coloured V75 PVC to AS/NZS 3808

Sheath: Coloured 4V75 PVC to AS/NZS3808

Relevant Standard: AS/NZS1125, AS/NZS1574, AS/NZS3808



Current Code	New Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Electrical Resistance @ 20°c (0/KM)	Nominal OD
LPC44	SPCS-4/4	2	4	56/0.3	5	13.6
LPC26/24*	SPCS-26/24	2/2	6	84/0.3	3.3	14.2
		2/2	4	56/0.3	5	14.2

* MTO - please enquire