

Control Cable (HMC)

450/750V V90HT PVC insulated

Applications

Cable used in Control, Signal, Lighting and Entertainment.

Product Specifications

Construction:

Conductor: Tinned Class 102 stranded copper to AS/NZS1574

Insulation: Coloured V90HT PVC to AS/NZS 3808

Sheath: Coloured V90HT PVC to AS/NZS3808 - Grey

Relevant Standard : AS/NZS5000.3, AS/NZS5000.1, AS/NZS1574, and AS/

NZS3808 **Core Configuration:** White Numbered Cores with a Green/Yellow Earth

**** Note:** We also do these cables with NO EARTH (NE)

Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Electrical Resistance @ 20°c (Ω/KM)	Nominal OD
HMC02/0.5	2	0.5	16/0.2	39	6.6
HMC03/0.5	3	0.5	16/0.2	39	6.9
HMC04/0.5	4	0.5	16/0.2	39	7.5
HMC05/0.5	5	0.5	16/0.2	39	8.1
HMC07/0.5	7	0.5	16/0.2	39	8.9
HMC12/0.5	12	0.5	16/0.2	39	11.5
HMC18/0.5	18	0.75	16/0.2	39	13.5
HMC03/0.75	3	0.75	24/0.2	26	7.5
HMC04/0.75	4	0.75	24/0.2	26	8.1
HMC05/0.75	5	0.75	24/0.2	26	8.9
HMC07/0.75	7	0.75	24/0.2	26	9.7
HMC12/0.75	12	0.75	24/0.2	26	12.5
HMC18/0.75	18	0.75	24/0.2	26	14.7
HMC25/0.75	25	0.75	24/0.2	26	17.3
HMC04/1.0	4	1	32/0.2	19.5	8.6
HMC05/1.0	5	1	32/0.2	19.5	9.2
HMC07/1.0	7	1	32/0.2	19.5	10.3
HMC09/1.0	9	1	32/0.2	19.5	11.9
HMC12/1.0	12	1	32/0.2	19.5	12.8
HMC18/1.0	18	1	32/0.2	19.5	15.5
HMC02/1.5	2	1.5	30/0.25	13.3	7.9
HMC03/1.5	3	1.5	30/0.25	13.3	8.3
HMC04/1.5	4	1.5	30/0.25	13.3	9.1
HMC05/1.5	5	1.5	30/0.25	13.3	10.0
HMC07/1.5	7	1.5	30/0.25	13.3	10.9
HMC12/1.5	12	1.5	30/0.25	13.3	14.2
HMC19/1.5	19	1.5	30/0.25	13.3	16.5
HMC27/1.5	27	1.5	30/0.25	13.3	19.9
HMC03/2.5	3	2.5	54/0.25	8	10.3
HMC04/2.5	4	2.5	54/0.25	8	11.4
HMC07/2.5	7	2.5	54/0.25	8	13.7
HMC12/2.5	12	2.5	54/0.25	8	18.0
HMC19/2.5	19	2.5	54/0.25	8	21.2