

**TYCAB AUSTRALIA PTY LTD**

A.B.N. 43 100 305 833

A.C.N. 100 305 833

269 FRANKSTON-DANDENONG ROAD
(LOCKED BAG 1413)

DANDENONG STH VICTORIA 3164

TELEPHONE 03 (Int. 613) 8791 0300

FAX - ADMIN 03 (Int. 613) 9794 0031

CUSTOMER SERVICE

PHONE 03 (Int. 613) 8791 0333

FAX 03 (Int. 613) 9791 8732

www.tycab.com.au**PRODUCT SPECIFICATION****1. PRODUCT CODE:** FFR22402**2. DESCRIPTION** 2 Core Parallel Webbed (Figure 8) 24/.2 (0.75 mmsq). P.A.C.W.
V90 P.V.C insulated, 250/250 volt to AS/NZS 3191.
ESV approval V98005
Oxygen Free copper. RoHS compliant PVC.**3. CONSTRUCTION****3.1 CONDUCTOR:** 24 strands of 0.2mm nom. Plain Annealed Copper to AS/NZS 1125
drawn from Class 110 copper to AS/NZS 1574.

Max. D.C. resistance at 20C: 26.7 ohms / km

3.2 INSULATION: Coloured V90 P.V.C. to AS/NZS 3808
Parallel Webbed (Figure 8) construction

Nominal Diameter: 2.8 x 6.0 mm

Nominal Wall Thickness: 0.8 mm

3.3 IDENTIFICATION: Printed on the insulation at nominally 500mm intervals:**TYCAB V90 APP V98005 250/250V AUSTEL APP**