

Lan Cables (DPA, DPZ, DPAS, DPXA)

HDPE Insulated UTP, FTP, STP and External rated

Applications

CCTV, Network Solutions, Access Control, Data Transmission.

Product Specifications

Construction:

Conductor: Plain Annealed Copper to AS1125

Drawn from Class 110A Copper AS/NZS1574

Insulation: Coloured HDPE Insulation

Sheath: CAT6 Coloured V75 PVC to AS/NZS3808

CAT5 - Coloured V75 PVC to AS/NZS3808

CAT6A Shielded - Coloured V75 PVC to AS/NZS3808

CAT6 Exterior and Screened - LDPE Sheath

Relevant Standard: AS/NZS1125, AS/NZS1574, AS/NZS3808

Available Colours :

Red ● White ○ Grey ● Yellow ●
Violet ● Black ● Blue ● Green ●



Current Code	New Code	No of Pairs	Nominal Area (mm ²)	Strand No. / Size	Electrical Resistance @ 20°c (0/100 KM)	Nominal OD
CAT6						
DPA81051	DPA04P-UTP	4	0.5	1/0.55	9.5	6.2
CAT6A Shielded						
DPXA81051*	DPAX04P-UTP	4	0.5	1/0.55	7.2	7.5
CAT6 External						
DPA81051EXT	DPA04P-UTP-EXT	4	0.5	1/0.55	9.5	7.5
CAT6 External Screened						
DPAS81051	DPAS04P-UTP	4	0.5	1/0.55	9.38	7.4
CAT5						
DPZ81051	DPZ04P-UTP	4	0.21	1/0.21	10	4.9

* MTO please enquire

#allyourcablesorted