

SINGLE CORE FLEXIBLE CABLE

PAGE 1/2

APPLIANCE WIRE 0.6/1KV

PAGE 3

APPLIANCE WIRE 240V

PAGE 4

SINGLE INSULATED POWER FLEX 0.6/1KV

PAGE 5

DOUBLE INSULATED POWER FLEX 0.6/1KV

PAGE 6/7

110°C DOUBLE INSULATED POWER FLEX 0.6/1KV

PAGE 8

HOOK UP WIRE



Appliance Wire (FVK)

0.6/1kV V90HT PVC Insulated (105°C)

Applications

Electrical Interconnections

Product Specifications

Construction:

Conductor: Tinned Annealed Copper to AS1125

Drawn from Class 102 Copper AS1574

Insulation: Coloured V90HT PVC to AS/NZS 3808

Sheath: N/A

Relevant Standard: AS/NZS3191

Available Colours:

- | | | | |
|---|--------|---|--------|
|  | Red |  | Black |
|  | Blue |  | Brown |
|  | Green |  | Violet |
|  | Yellow |  | Orange |
|  | White |  | Grey |

**Stripes Available by Request.*



Current Code	New Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Amp Rating @ 30°c	Electrical Resistance @ 20°c (Ω/KM)	Nom OD
FVK11602	FSVH-0.5T	1	0.5	16/0.2	3	40.1	2.6
FVK12402	FSVH-0.75T	1	0.75	24/0.2	7.5	25.7	2.8
FVK13202	FSVH-1.5T	1	1	32/0.2	10	20	3.0
FVK130025	FSVH-1T	1	1.5	30/0.25	15	13.7	3.15
FVK150025	FSVH-2.5T	1	2.5	50/0.25	20	8.2	3.8
FVK15603	FSVH-4T	1	4	56/0.3	25	5.1	4.75
FVK18403	FSVH-6T	1	6	84/0.3	30	3.4	5.3

Low Smoke-Zero Halogen Appliance Wire (FLSZH)

0.6/1kV X-HF-110 PVC Insulated (110°C)

Applications

Electrical Interconnections

Product Specifications

Construction:

Conductor: Tinned Annealed Copper to AS/NZS1125

Drawn from Class 102 Copper AS/NZS1574

Insulation: Coloured X-HF-110 PVC to AS/NZS 3808

Sheath: N/A

Relevant Standard: AS/NZS319, AS/NZS 5000.1, AS/ZS1660.5.1-4

Available Colours:

- | | |
|--|--|
|  Red |  Black |
|  Blue |  Brown |
|  Green |  Violet |
|  Yellow |  Orange |
|  White |  Grey |

**Stripes Available by Request.*



Current Code	New Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Amp Rating @ 30° c	Electrical Resistance @ 20° c (Ω/KM)	Nom OD
FLSZH11602	FLSZH-0.5T	1	0.5	16/0.2	3	40.1	2.6
FLSZH12402	FLSZH-0.75T	1	0.75	24/0.2	7.5	25.7	2.8
FLSZH13202	FLSZH-1.5T	1	1	32/0.2	10	20	3.0
FLSZH130025	FLSZH-1T	1	1.5	30/0.25	15	13.7	3.15
FLSZH150025	FLSZH-2.5T	1	2.5	50/0.25	20	8.2	3.8
FLSZH15603	FLSZH-4T	1	4	56/0.3	25	5.1	4.75
FLSZH18403	FLSZH-6T	1	6	84/0.3	30	3.4	5.3

Appliance Wire (FVT)

250/440V V90HT PVC Insulated

Applications

Wiring of Communications, Electronic Equipment and Switchboards

Product Specifications

Construction:

Conductor: Annealed Copper to AS1125 Drawn from Class 102 Copper AS1574

Insulation: Coloured V90HT PVC to AS/NZS 3808

Sheath: N/A

Relevant Standard: AS/NZS3191

Available Colours:

- | | |
|--|--|
| ● Red | ● Black |
| ● Blue | ● Brown |
| ● Green | ● Violet |
| ● Yellow | ● Orange |
| ○ White | ● Grey |

**Stripes Available by Request.*



Current Code	New Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Amp Rating @ 30 °c	Electrical Resistance @ 20 °c (0/KM)	Nom OD
FVT11602	FSVO-0.5T	1	0.5	16/0.2	3	40.1	2.2
FVT12402	FSVO-0.75T	1	0.75	24/0.2	7.5	25.7	2.4
FVT13202	FSVO-1T	1	1	32/0.2	10	20	2.6

Single Insulated Power Flex (ZBD)

0.6/1KV PVC insulated 105°cc

Applications

Power Cable (Fixed Applications)

Product Specifications

Construction:

Conductor: Annealed Copper to AS1125 Drawn from Class 110A Copper AS1574

Insulation: Coloured V90HT PVC to AS/NZS 3808

Sheath: N/A

Relevant Standard: AS/NZS 5000.1:2005

Available Colours:

- Black,
- White
- Red
- Blue
- Green/Yellow



Current Code	New Code	No. of Cores	Nominal Area (mm)	Strand No. / Size	Amp Rating @ 30°c	Electrical Resistance @ 20°c (0/KM)	Nom OD	Voltage Drop 1 Phase	Voltage Drop 3 Phase
ZBD112802	ZSVH-4	1	4	128/0.2	40	5	4.8	1.29	1.12
ZBD119202	ZSVH-6	1	6	192/0.2	51	3.3	5.4	7.5	6.49
ZBD132202	ZSVH-10	1	10	322/0.2	69	1.91	6.3	4.45	3.86
ZBD151102	ZSVH-16	1	16	511/0.2	92	1.21	7.3	2.8	2.43
ZBD179202	ZSVH-25	1	25	784/0.2	125	0.78	8.8	1.78	1.54
ZBD1112102	ZSVH-35	1	35	1120/0.2	155	0.554	10.2	1.29	1.12
ZBD1159602	ZSVH-50	1	50	1568/0.2	185	0.386	11.9	0.96	0.834
ZBD1221202	ZSVH-70	1	70	2240/0.2	240	0.272	14	0.62	0.589
ZBD1302102	ZSVH-95	1	95	3040/0.2	295	0.206	16	0.51	0.439
ZBD1382102	ZSVH-120	1	120	3800/0.2	345	0.161	17.5	0.41	0.359

Double Insulated Power Flex (ZDU)

0.6/1KV PVC insulated, Nitrile Modified Sheath 105°C

Applications

Power: Switchboards, Busbars, Transformers

Product Specifications

Construction:

Conductor: Annealed Copper to AS1125 Drawn from Class 110A Copper AS1574

Insulation: Nitrile (NBR) Modified PVC TO AS3808

Sheath: Nitrile (NBR) Modified PVC TO AS3808

Relevant Standard: AS/NZS 5000.1:2005

Minimum Bending Radius: Fixed 4 x cable diameter, Flexing 6 x cable diameter

Available Colours:

● Orange ● Black ● Red



Current Code	New Code	No. of Cores	Nominal Area (mm)	Strand No. / Size	Amp Rating @ 30°C	Electrical Resistance @ 20°C (0/KM)	Nom OD	Voltage Drop 1Phase	Voltage Drop 3 Phase
ZDU132202	ZDVT-10	1	10	322/0.2	69	1.91	9.1	4.45	3.86
ZDU151102	ZDVT-16	1	16	511/0.2	92	1.21	10.1	2.8	2.43
ZDU179202	ZDVT-25	1	25	784/0.2	125	0.78	11.8	1.78	1.54
ZDU1112102	ZDVT-35	1	35	1120/0.2	155	0.554	13.1	1.29	1.12
ZDU1159602	ZDVT-50	1	50	1568/0.2	185	0.386	14.9	0.96	0.834
ZDU1221202	ZDVT-70	1	70	2240/0.2	240	0.272	17	0.62	0.589
ZDU1302102	ZDVT-95	1	95	3040/0.2	295	0.206	19.3	0.51	0.439
ZDU1382102	ZDVT-120	1	120	3800/0.2	345	0.161	20.8	0.41	0.359

Double Insulated Power Flex (ZDXU)

0.6/1KV R-E-110 Insulated, Nitrile Modified Sheath 105°C

Applications

Power: Switchboards, Busbars, Transformers

Product Specifications

Construction:

Conductor: Annealed Copper to ASI 125 Drawn from Class I 10A Copper ASI 574

Insulation: R-E-110 to AS/NZS 3808

Sheath: Nitrile (NBR) Modified PVC TO AS3808

Relevant Standard: AS/NZS 5000.1:2005

Minimum Bending Radius: Fixed 4 x cable diameter, Flexing 6 x cable diameter

Available Colours:

● Orange ● Black



Current Code	New Code	No. of Cores	Nominal Area (mm)	Strand No. / Size	Amp Rating @ 30°C	Electrical Resistance @ 20°C (0/KM)	Nom OD	Voltage Drop 1 Phase	Voltage Drop 3 Phase
ZDXU132202	ZDRT-10	1	10	322/0.2	105	1.91	9.1	4.97	4.30
ZDXU151102	ZDRT-16	1	16	511/0.2	135	1.21	10.1	3.13	2.7
ZDXU179202	ZDRT-25	1	25	784/0.2	185	0.78	11.8	1.99	1.72
ZDXU1112102	ZDRT-35	1	35	1120/0.2	225	0.554	13.1	1.44	1.24
ZDXU1159602	ZDRT-50	1	50	1568/0.2	275	0.386	14.9	1.07	0.92
ZDXU1221202	ZDRT-70	1	70	2240/0.2	350	0.272	17	0.769	0.65
ZDXU1302102	ZDRT-95	1	95	3040/0.2	435	0.206	19.3	0.567	0.48
ZDXU1382102	ZDRT-120	1	120	3800/0.2	510	0.161	20.8	0.465	0.39

Double Insulated Power Flex (LHDN)

0.6/1KV X-HF-110 Insulated, Nitrile Modified Sheath 105°C

Applications

Power: Switchboards, Busbars, Transformers

Product Specifications

Construction:

Conductor: Annealed Copper to AS1125 Drawn from Class 110A Copper AS1574

Insulation: X-HF-110 to AS/NZS 3808

Sheath: Nitrile (NBR) Modified PVC TO AS3808

Relevant Standard: AS/NZS 5000.1:2005

Minimum Bending Radius: Fixed 4 x cable diameter, Flexing 6 x cable diameter

Available Colours:

● Orange ● Black



Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Amp Rating @ 30°C	Electrical Resistance @ 20°C (.0/KM)	Nominal OD
LHDN150	1	150	322/0.2	450	0.129	23.0
LHDN185	1	185	511/0.2	516	0.106	26.1
LHDN240	1	240	784/0.2	620	0.0801	29.3
LHDN300	1	300	1120/0.2	714	0.0641	32.0
LHDN400	1	400	1568/0.2	855	0.0486	36.2
LHDN500*	1	500	2240/0.2	990	0.0384	40.0
LHDN630*	1	630	3040/0.2	1154	0.0287	42.5

*MTO - please enquire

Hook Up Wire (HVT)

V90HT PVC insulated

Applications

Control Panels, Automotive, Meters, Ovens, and Internal Wiring

Product Specifications

Construction:

Conductor: Plain Annealed Copper to

Drawn from Class 102 Copper AS1574

Insulation: Coloured V90HT PVC to AS/NZS 3808

Sheath: N/A

Relevant Standard: AS/NZS1574, AS3808

Available Colours:

- | | | | |
|--|---|--|---|
|  Black |  Green |  Blue |  Brown |
|  Orange |  Pink |  Red |  Grey |
|  Violet |  White |  Yellow | |



Current Code	New Code	No. of Cores	Nominal Area (mm ²)	Strand No. / Size	Amp Rating @ 30 °c	Electrical Resistance @ 20 °c (Ω/KM)	Nominal OD
HVT1702	HVT01/0.20	1	0.2	7/0.2	0.3	89	1.2
HVT17025*	HVT01/0.34	1	0.34	7/0.25	0.7	57.4	1.6
HVT110025	HVT01/0.5ULC	1	0.5	10/0.25	2.0	38	1.8
HVT1110	HVT01/0.75	1	0.75	1/1.0	4.6	22.5	2.35

* MTO - please enquire